

MAX200[®] HIGH CAPACITY, DUAL GAS PLASMA CUTTING SYSTEM

**For Cutting Gauge
To 2-Inch (50 mm) Metals**

HYPERTHERM[®]



Hypertherm is ISO 9001 registered

HIGH PRODUCTIVITY . . . LOW COST OPERATION . . . DUAL GAS CAPABILITIES: THE MAX200 FROM HYPERTHERM IS THE ANSWER TO YOUR HEAVY-DUTY, HIGH CAPACITY METAL CUTTING NEEDS.

The MAX200 continues Hypertherm's tradition of combining advanced technology and superior quality to deliver operating advantages that are unmatched in the industry.

THE MAX200 ADVANTAGE...

- 200 amp, 30 kw power output delivers heavy-duty cutting capacity up to 2 inches (50 mm) thick on most metals; typical cutting speeds greatly exceed oxyfuel or other methods.
- 100% duty cycle at full power keeps you cutting — all day long.
- Adjustable power output from 40 to 200 amps lets the operator precisely match power to cutting requirements.
- A state-of-the-art transistorized power supply maintains constant output current regardless of variations in input voltages or torch-to-work distances, ensuring clean, square cuts throughout the cutting range.
- MAX200's dual gas system — plasma and shield — allows you to run on Air/Air, O₂/Air, N₂/Air, N₂/CO₂, Ar-H₂/N₂ or other combinations for optimal results on all metals and conditions.



- The MAX200's patented shielded torch front-end practically eliminates the possibility of double arcing, greatly enhancing piercing capabilities and extending consumable parts life.

- The water-cooled torch provides maximum cooling, another factor behind MAX200's long consumable parts life; the cooling system is built into the power supply for exceptional convenience.

- The MAX200 can be used on cutting machines or for hand-held applications.

- A machine motion delay control comes built into every system.

- Optional Torch Height Control (THC) and inductive Initial Height Sensing (IHS) are available for machine use.

- New consumables, an optional extended torch and heat shield, optimize the MAX200 for gouging applications.

- A full set of easy-to-read indicator/diagnostic lights monitor the status of external door panels, transformer and chopper temperature, coolant level, plasma and shield gas pressure, coolant temperature, and coolant flow, greatly simplifying troubleshooting.



- Extended leads up to 150' (45 m) are available for both hand-held and mechanized systems for added flexibility.

- Safety interlocks are built in, ensuring maximum operator safety.

- MAX200 comes equipped with casters for easy wheeling, and there is a lifting eye located at the balance point for use with cranes.

- A full two-year warranty on the power supply and one-year coverage on the torch backs up Hypertherm's quality commitment.



**MAX200
FROM HYPERTHERM . . .
APPLYING TECHNOLOGY
TO MEET TODAY'S
METAL CUTTING NEEDS**

MAX200 HEAVY-DUTY PLASMA CUTTING SYSTEM

MAX200 SYSTEM COMPONENTS:

- Power Supply
- Torch Assembly
- 25'/50' (7.5 m/15 m) Torch Leads
- Consumable Parts Kit
- 25' (7.5 m) Work Cable with Clamp
- Torch Coolant



SPECIFICATIONS:

Model Number: MAX200
***Input Voltage:** 220/380/415 V, 3Ph, 50/60 Hz
 240/480 V, 3Ph, 60 Hz, CSA
 400V, 3Ph 50 Hz, CE Certified
Input Current: 90/45 A, 240/480 V
 @ 30 kw Output
 98/57/52 A,
 220/380/415 V
 @ 30 kw Output
Output Voltage: 150 V DC
Output Current: 40 to 200 A
Duty Cycle: 100%
Maximum OCV: 280 V DC
Dimensions : 41" (1040 mm) Depth
 28" (710 mm) Width
 43" (1090 mm) Height
Weight: 780 lbs (350 kg)
Gas Supply:
Plasma Gas: Air, N₂, O₂, Ar-H₂
Plasma Flow (Air): 66 scfh (31 l/min)
Plasma Pressure: 120 psig (8.3 bar)
Shield Gas: Air, N₂, CO₂
Shield Gas Flow (Air): 280 scfh (132 l/min)
Shield Gas Pressure: 90 psig (6.2 bar)

*NOTE: OTHER VOLTAGES AVAILABLE

For more information about the MAX200 Heavy-Duty cutting System, Call us today, TOLL FREE in the USA and Canada:

1-800-643-0030

www.hypertherm.com

© Copyright 12/04 Hypertherm, Inc. Revision 0
English 860100

OPERATING DATA:

Maximum Cutting Capacity: 2" (50 mm)

Recommended Maximum Mechanized Production Capacity: 1" (25 mm)

MATERIAL	THICKNESS		CURRENT (A)	APPROXIMATE TRAVEL SPEED	
	(inches)	(mm)		(ipm)	(mm/min)
MILD STEEL	1/4	6	200	135	3400
	3/8	10	200	105	2700
	1/2	12	200	85	2200
	3/4	19	200	55	1400
	1	25	200	35	900
	1 1/4	32	200	20	500
	1 1/2	38	200	13	330
	2	50	200	6	150
ALUMINUM	3/16	5	200	220	5600
	1/4	6	200	190	4800
	3/8	10	200	145	3700
	1/2	12	200	110	2800
	3/4	19	200	65	2200
	1	25	200	35	900
	1 1/4	32	200	20	500
	1 1/2	38	200	12	300
STAINLESS	3/16	5	200	220	5600
	1/4	6	200	195	5000
	3/8	10	200	145	3700
	1/2	13	200	105	2700
	3/4	19	200	55	1400
	1	25	200	30	760
	1 1/4	32	200	15	380
	1 1/2	38	200	10	250

Hypertherm, HT, HyFlow, LongLife, PAC and Command are trademarks of Hypertherm, Inc. and may be registered in the United States and/or other countries.

Hypertherm®

The world leader in
plasma cutting technology™

Hypertherm, Inc. USA 603-643-3441 Tel 603-643-5352 Fax manual.info@hypertherm.com
Hypertherm Automation, LLC USA 603-298-7970 Tel 603-298-7977 Fax info@hyperthermautomation.com
Hypertherm Plasmatechnik, GmbH Deutschland 49 6181 58 2100 Tel 49 6181 58 2134 Fax HTDeutschland.info@hypertherm.com
Hypertherm (S) Pte Ltd. Singapore 65 6 841 2489 Tel 65 6 841 2490 Fax HTSingapore.info@hypertherm.com
Hypertherm (Shanghai) Consulting Co., Ltd. P.R. China 86 21 5835 5362 /3 Tel 86 21 5835 5220 Fax HTChina.info@hypertherm.com
Hypertherm Branch of Hypertherm UK, LLC England 00 800 3324 9737 Tel 00 800 4973 7329 Fax HTUK.info@hypertherm.com
France 00 800 3324 9737 Tél 00 800 4973 7329 Fax HTFrance.info@hypertherm.com
Hypertherm S.r.l. Italia 39 02 725 46 312 Tel 39 02 725 46 400 Fax HTItalia.info@hypertherm.com
Hypertherm Europe B.V. Nederland 31 165 596907 Tel 31 165 596901 Fax HTEurope.info@hypertherm.com
Japan 81 0 559 75 7387 Tel 81 0 559 75 7376 Fax HTJapan.info@hypertherm.com
HYPERTHERM BRASIL LTDA. 55 11 6482 1087 Tel 55 11 6482 0591 Fax HTBrasil.info@hypertherm.com