

COMPACT IN-SHOP MODELS



Model 125
125 POUND CAPACITY
- for operation on 115
Volt, AC.



Model 350
350 POUND CAPACITY - for
operation on 115 Volt, AC.
Also available: Model 350 A for
operation on 220/440 Volt, AC.



**Compact...
and
stackable!**

These Stabilizing Ovens have gained international recognition and acceptance based on a variety of quality and performance features including....

- compact, modular design with controls recessed for protection.
- shelves easily removed to accommodate large size loads.
- oven fully insulated to prevent heat loss....pilot light indicates oven operation.
- thermostat control, incorporating on/off switch, maintains oven temperature in 100° - 550° F range.
- models 125 and 350 feature nesting feet and sockets for safe, easy stacking.

Thermometer Accessory -

Model T23 - thermometer with a mounting bracket and screw for front mounting on the Model 125 and 350 ovens.

ELECTRODE STABILIZING OVENS

SPECIFICATIONS

	PORTABLE OVENS				COMPACT IN-SHOP MODELS			
	10 A-20	10 B-20	10 N-20	50	125	350	350A	1000
Capacity	10 to 20 lbs			50 to 70 lbs.	125 to 175 lbs.	350 to 400 lbs.		Sixteen 12" Spools/1000 lbs.
Outside Dimensions	7" dia. x 23" high			11" dia. x 23" high	16"h x 16" w x 24 1/2"d	22"h x 22"w x 24 1/2" d		39 3/4"h x 30 1/4"w x 30 3/4"d
Inside Dimensions	3" dia. x 19" high			7" dia. x 19" high	8 1/4"h x 9 3/4"w x 19"d	14"h x 16"w x 19"d		24"h x 21 3/4"w x 24"d
Unit Weight (approx.)	14 lbs.			32 lbs.	58 lbs	105 lbs.		330 lbs.
Electrode Size	up to 18"			up to 18"	up to 18"	up to 18"		up to 24"
Line Cord	3 wire - 8 ft.			3 wire- 8 ft.	3 wire - 8 ft.	3 wire - 8 ft.	None	None
Element	100W - 115 Volt	125W - 115 Volt	300W - 115 Volt	300 W - 115 Volt	1000 W - 115 V	1500 W - 115 V	1500 W-220/440 V	3000 W - 220/440 V- 1 Phase
Thermostat	No	Yes	Yes (2)	Yes	Yes	Yes		Yes
Pilot Light	Yes			Yes	Yes	Yes		Yes
Temp. Range	Av. 275° F	100° - 400° F		100° - 400° F	100° - 550° F	100° - 550° F		100° - 550° F
Door Latch	Lift Lid			Lift Lid	Push/Pull	Push/Pull		Push/Pull
Stacking	No			No	Yes	Yes		Yes

ALL SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE

Note: Weight capacity depends on electrode length.