

POWER MIG® 180C



Processes

MIG, Flux-Cored

Product Number

K2473-2

See back for complete specs

Input Power

208/230/1/60

Input Current at Rated Output

20A

Rated Output Current/Voltage/Duty Cycle

208V: 130A/17V/30%

230V: 130A/20V/30%

Output Range

30-180 Amps DC, Max. OCV: 34

Wire Feed Speed Range

50-500 ipm (1.3-12.7 m/min)

Weight/Dimensions (H x W x D)

66 lbs. (30 kg)

14 x 10.2 x 18.6 in
(357 x 258 x 472 mm)

POWER MIG®

The Professional's Choice.™

Whether you're a farmer or a fabricator, an autobody shop or a backyard mechanic, the POWER MIG® 180C will help you get the job done! It's a portable wire welder designed for use with industrial 230 volt input power, so you can weld on thicker material – up to 3/16 in. with MIG welding and 1/2 in. with gas-less flux-cored welding.

FEATURES

- ▶ **Diamond Core Technology™** – Delivers a forgiving arc, excellent out-of-position arc action, low spatter and a wide voltage sweet spot at a given wire feed speed for steel, stainless steel or aluminum.
- ▶ **Industrial Cast Aluminum Drive** – Dual gear-driven drive rolls deliver positive traction. Patented split wire guides ensure optimal wire alignment and a brass-to-brass gun connection aids critical conductivity. A large industrial closed-design drive motor improves torque and enhances trouble-free performance.
- ▶ **No Hassle Tool-less Design** – For input power changes, wire spool mounting, wire drive service and polarity changes.
- ▶ **Spool Gun Ready** – Just remove the standard MIG gun and plug in the economical Magnum® PRO 100SG spool gun (optional) for enhanced aluminum wire feeding performance.
- ▶ **Toughest PC Board Protection in the Industry** – 'Potted' to seal sensitive components from the environment, 'trayed' in a tough plastic tray to add rigidity and shock resistance.

APPLICATIONS

- ▶ Metal Fabrication
- ▶ Maintenance and Repair
- ▶ Autobody/Farm
- ▶ Light Industrial



Shown: K2473-2

WHAT'S INCLUDED

K2473-2 Includes:

- ▶ Magnum® PRO 100L gun, 10 ft. (3.0 m)
- ▶ Gas and Gasless Nozzles
- ▶ Cable Liner
- ▶ .025 in. (0.6 mm) and .035 in. (0.9 mm) Contact Tips
- ▶ Work Cable and Clamp
- ▶ Adjustable Gas Regulator and Hose
- ▶ Spindle Adapter
- ▶ Sample Spool of .025 in. (0.6 mm) SuperArc® L-56 Mild Steel MIG Wire
- ▶ Sample Spool of .035 in. (0.9 mm) Innershield® NR-211-MP Flux-Cored Wire
- ▶ Learn-To-Use DVD
- ▶ .035 in. (0.9 mm) and .025 - .030 in. (0.6 - 0.7 mm) Drive Rolls
- ▶ .030 - .045 in. (0.7 - 1.1 mm) Knurled Drive Roll
- ▶ .025 - .035 in. (0.6 - 0.9 mm) and .035 - .045 in. (0.9 - 1.1 mm) Wire Guides

INPUT



OUTPUT



Two Year Extended
Warranty Available in
the U.S.A. and Canada



PERFORMANCE PLUS

POWER MIG® 180C Welding Capabilities

Process	Wire Dia. (in.)	Wire Diameter																	
		24ga.	22ga.	20ga.	18ga.	16ga.	14ga.	12ga.	10ga.	3/16"	1/4"	5/16"	3/8"	1/2"					
Flux-Cored Welding – Steel	.030																INNERSHIELD® NR-211-MP	SP	MP
	.035																INNERSHIELD® NR-211-MP	SP	MP
	.045																INNERSHIELD® NR-212	SP	MP
MIG Welding – Steel	.025																SUPERARC® L-56	SP	
	.030																SUPERARC® L-56	SP	
	.035																SUPERARC® L-56	SP	
MIG Welding – Aluminum	.035																SUPERGLAZE® 4043	SP	

SP = Single Pass
MP = Multiple Pass

L12603-5



KP2529-2 Shown

DRIVE ROLL AND WIRE GUIDES		
Product Number	Wire Diameter in. (mm)	Type/Process
Drive Rolls		
KP2529-1	.025 - .030 (0.6 - 0.8)	Smooth/MIG
KP2529-2	.035 (0.9)	Smooth/MIG
KP2529-3	.030 - .045 (0.8 - 1.1)	Knurled/Flux-Cored
Inner Wire Guides		
KP2531-1	.025 - .035 (0.6 - 0.9)	All
KP2531-2	.045 (1.1)	All

RECOMMENDED ACCESSORIES

GENERAL OPTIONS



Welding Cart

Full-featured cart is designed to store and transport a welder, 80 cubic foot gas cylinder, welding cables and accessories. Includes an angled top shelf for easy access to welder controls, a lower tray for added storage space, a sturdy handle and a convenient cable wrap hanger.

Order **K2275-1**



Utility Cart

Heavy duty cart stores and transports welder, 150 cubic foot shielding gas cylinder, welding cables and accessories. Includes stable platforms for welder and gas bottle platform, lower tray for added storage capacity and adjustable height handle.

Order **K520**



Small Canvas Cover

Protect your welder when not in use. Made from attractive red canvas that is flame retardant, mildew resistant and water repellent. Includes a convenient side pocket to hold your welding torch or gun.

Order **K2377-1**



Spot Timer Kit

This timer allows you to set a fixed weld time of up to 10 seconds that is initiated when you pull the gun trigger. Ideal for making consistent spot welds on thin sheet metal.

Order **K2525-1**



Accessory Bag

Canvas bag can be used to store your welding accessories and tools.

Order **K3071-1**



WIRE FEEDER OPTIONS

Magnum® PRO 100SG Spool Gun

Designed to easily feed 4 in. (102 mm) diameter 1 lb. (0.45 kg) spools of .030 in. (0.8 mm) or .035 in. (0.9 mm) diameter SuperGlaze® aluminum MIG wire. Includes gun, adapter kit, .035 in. (0.9 mm) contact tips (qty. 3), gas nozzle, and a 1 lb. (0.45 kg) spool of SuperGlaze® 4043 .035 in. (0.9 mm) MIG wire. Packaged in a convenient carrying case.

Order **K3269-1**



Welding Fume Extractors

Lincoln offers a wide variety of welding fume extraction environmental system solutions, ranging from portable systems easily wheeled around the shop to shop-wide central systems servicing many dedicated welding stations.

Request Publication **E13.40**

PRODUCT SPECIFICATIONS

Product Name	Product Number	Input Power	Rated Output Current/Voltage/Duty Cycle	Input Current @ Rated Output	Output Range	H x W x D inches (mm)	Net Weight lbs. (kg)
POWER MIG® 180C	K2473-2	208/230/1/60	130A/17V/30% 130A/20V/30%	20A	30-180 Amps DC 50-500 ipm WFS (1.3-12.7 m/min) Max. OCV: 34	14 x 10.15 x 18.6 (357 x 258 x 472)	66 (30)

For best welding results with Lincoln Electric equipment, always use Lincoln Electric consumables. Visit www.lincolnelectric.com for more details.

CUSTOMER ASSISTANCE POLICY

The business of The Lincoln Electric Company is manufacturing and selling high quality welding equipment, consumables, and cutting equipment. Our challenge is to meet the needs of our customers and to exceed their expectations. On occasion, purchasers may ask Lincoln Electric for information or advice about their use of our products. Our employees respond to inquiries to the best of their ability based on information provided to them by the customers and the knowledge they may have concerning the application. Our employees, however, are not in a position to verify the information provided or to evaluate the engineering requirements for the particular weldment. Accordingly, Lincoln Electric does not warrant or guarantee or assume any liability with respect to such information or advice. Moreover, the provision of such information or advice does not create, expand, or alter any warranty on our products. Any express or implied warranty that might arise from the information or advice, including any implied warranty of merchantability or any warranty of fitness for any customers' particular purpose is specifically disclaimed.

Lincoln Electric is a responsive manufacturer, but the selection and use of specific products sold by Lincoln Electric is solely within the control of, and remains the sole responsibility of the customer. Many variables beyond the control of Lincoln Electric affect the results obtained in applying these types of fabrication methods and service requirements.

Subject to Change – This information is accurate to the best of our knowledge at the time of printing. Please refer to www.lincolnelectric.com for any updated information.

LINCOLN
ELECTRIC
THE WELDING EXPERTS®