

Red-D-Arc Welderentals®

When you're ready to weld.

Red-D-Arc Welderentals, an Airgas company, is North America's leading provider of rental welding products and services, with over 50,000 units in a fleet that includes welders, welding positioners and other welding-related equipment, for almost any type of welding process and application.

Sullair 375HH Portable Air Compressor



HIGH PRESSURE MODEL

375 CFM AT 200 PSIG CAPACITY

ROTARY SCREW COMPRESSOR

0 TO 100% CAPACITY CONTROL

SSAM - SHUTDOWN SYSTEM

John Deere 4045HF285 POWERED



Airgas

1-866-733-3272
Rental Centers Across North America

Sullair 375HH Portable Air Compressor

Output

375 CFM at 200 PSIG capacity

0 to 100% Capacity Control

Pneumatic inlet valve and unloaded starting

Rotary Screw Compressor

Single-stage, fluid flooded, cast iron housing is dimensionally stable, thick walled and machined to close tolerances

Curbside Instrument Panel

Hinged, padlockable cover

Powerview gauge module with mechanical air pressure gauge

Rocker-type engine start switch

Idle warm-up valve

High/low pressure selector valve allows dual pressure capability without making mechanical adjustments

SSAM - Shutdown System and Annunciation Module

Shutdown with annunciator light for high compressor temperature, high engine-coolant temperature, low engine-oil pressure, and engine underspeed

Low-fuel shutdown

Three-Stage Dry Type Air Filters

Separate filters for engine and compressor

Integral Aftercooler

Removes most of the water vapor and solids from the compressed air discharge, providing clean, moisture-free air

AWF Compressor Fluid

All-weather, all-climate fluid

Improved hot and cold weather lubrication

Longer compressor fluid life

Highway Towable Running Gear

3" X 5" drawbar

Adjustable height hitch (15", 17", 19")

Quick-change hitch

Screw jack with pad

Transport security chains

Heavy duty leaf spring suspension

Quiet Operation

Meets US EPA sound requirements of 76 dBA @ 7 meters

Tier 3 Emission Compliant Engine

Specifications

DELIVERY @ RATED PRESSURE	375 CFM (177 L/S, 10.6 cubic meters/minute)
RATED PRESSURE	200 psig (14 bar)
PRESSURE RANGE	80 - 200 psig (5.5 - 14 bar)
WEIGHT	4,440 lb (2014 kg)
LENGTH (drawbar)	156.1" (3966 mm)
LENGTH (canopy)	98.8" (2510 mm)
WIDTH	77.2" (1960 mm)
HEIGHT	74" (1880 mm)
TRACK WIDTH	67.5" (1715 mm)
TIRE SIZE (load range)	H78 X 15 ST (D)

Engine

MAKE	John Deere
TYPE	Diesel, Tier 3 Emission Compliant
MODEL	4045HF285
DISPLACEMENT	275 cu in (4507 cc)
CYLINDERS	4
CYCLES	4
BORE AND STROKE	4.19" x 5.00" (106 mm x 127 mm)
RATED SPEED	2200 RPM
RATED POWER	140 HP (104 kW)